




RoHS

SPECIFICATION

Current Rating: 1Amp
Insulator Resistance: 5000 Megohms Min.
Contact Resistance: 20 Milliohms Max.
Dielectric Withstanding: AC 500V
Operating Temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
Max Processing Temp: 230°C For 60 Seconds
 260°C For 10 Seconds
Insulator Material: Polysphor, UL 94V-0
Standard: Nylon-9T
Contact Material: Phosphor Bronze.
Finish: Gold Flash All Over



Pc Board Layout



Cir- cuits	Dimension (mm)	
	L1	L2
2x2	2.00	4.00
2x3	4.00	6.00
2x4	6.00	8.00
2x5	8.00	10.00
2x6	10.00	12.00
2x7	12.00	14.00
2x8	14.00	16.00
2x9	16.00	18.00
2x10	18.00	20.00
2x11	20.00	22.00
2x12	22.00	24.00
2x13	24.00	26.00
2x14	26.00	28.00
2x15	28.00	30.00
2x16	30.00	32.00
2x17	32.00	34.00
2x18	34.00	36.00
2x19	36.00	38.00
2x20	38.00	40.00
2x21	40.00	42.00
2x22	42.00	44.00
2x23	44.00	46.00
2x24	46.00	48.00
2x25	48.00	50.00
2x26	50.00	52.00
2x27	52.00	54.00
2x28	54.00	56.00
2x29	56.00	58.00
2x30	58.00	60.00
2x31	60.00	62.00
2x32	62.00	64.00
2x33	64.00	66.00
2x34	66.00	68.00
2x35	68.00	70.00
2x36	70.00	72.00
2x37	72.00	74.00
2x38	74.00	76.00
2x39	76.00	78.00
2x40	78.00	80.00

立原科技有限公司
Easy Show Technology Corp.

Title: Female Header 2.0mm H:4.3
Daul Row, DIP Type, 180度

Tolerances		App.	Dabbie	Units	Part no:
Linear	Angles				
.X ± 0.30	X' $\pm 5^{\circ}$	Chk.	Kitty	☒	Dwg no:
.XX ± 0.20	X' $\pm 2^{\circ}$	Dr.	Eddy	☐	
.XXX ± 0.10	.XX' $\pm 1^{\circ}$	Date.	2007.09.12	Size A4	Sheet 1/1
Projection				Scale 1:1	